

# Triumph®

by IDEAL


## → TRIUMPH 4850

**AUTOMATIC CUTTER** · electric blade and clamp drive · automatic clamp can be lowered or raised independently from blade · spindle-guided back gauge with calibrated crank · precision back gauge measuring scale on front table · optical cutting line · dual side guides on front and rear tables · solid steel blade carrier · stand with storage shelf · **SAFETY FEATURES:** external blade depth adjustment · two-hand operation · transparent safety guards on front and rear tables · automatic blade and clamp return from any position · disc brake for instant blade stop · safety lock with key and main switch

Dimensions (D x W x H): 38 ¼ x 29 ¾ x 48 ½ inches, Shipping weight: 556 lbs.



### OPTICAL CUTTING LINE



An optical cutting line indicates exact location of cut and helps to perfectly position trim marks.

### REAR SAFETY GUARD



The transparent rear safety guard gives a clear view of side guides and back gauge.

### → TRIUMPH 4850

Cutting width	18 ¾"
Cutting height	3"
Narrow cut	1 ¼"
Cutting length behind blade	17 1/8"
Table length in front of blade	13 ¾"
Motor	2 hp
Power supply	115 V, 60 Hz*

\* 20 amp dedicated line required

Dealer:

**MBM**  
CORPORATION

3134 Industry Drive  
North Charleston, South Carolina 29418  
800-223-2508, fax: 843-552-2974  
[www.mbmcorp.com](http://www.mbmcorp.com)

**IDEAL.MBM**  
CORPORATION

1 Regan Road, unit 12  
Brampton, Ontario L7A 1B8  
800-387-2528, fax: 905-840-1114  
[www.ideal-mbm.com](http://www.ideal-mbm.com)

All technical data is approximate and subject to change. © MBM Corporation, 10/2006.